DPB-500 PUR

Specifications

ModelDPB-500 PUR

Floor model Туре

The Number of Clamp 1

Type of Binding Binding with a cover, binding without a cover

Booklet Size

Book Bisonaking thickness 1 to 51 mm +cover thickness Maximum size 360 (length) x 320 (height) mm Minimum size 120 (length) x 120 (height) mm Book block form Sheet, single-folded, double-folded

Paper type Fine 52 to 157 g/m

Art/Coated 79 to 157 g/m

Cover Feeding method Belt suction

(Separating air, separator manual non-step adjustment)

Maximum size 360 (length) x 696 (width) mm Minimum size 120 (length) x 250 (width) mm

Paper type Fine 81.4 to 302 g/m

Art/Coated 104.7 to 302 g/m

Stack height 70 mm

Maximum Binding Speed 525 cycle/hour Milling Maximum 4 mm (Manual 6 step adjustment: 0, 0.5, 1.0, 2, 3, 4 mm)

Roughening 2 pieces

Scoring The number of score

Each 2 on the operator's side and non-operator's side

(spine and hinge)

Depth adjustment Manual non-step adjustment

Ream weight 157g/m or more

Scoring width 3 to 51 mm

Nipping Height adjustment Manual non-step adjustment

Stacker Stacking method Vertical stack

Stack height Maximum 200 mm

Ratings Three-phase, 380 to 415 V, 50/60 Hz

Power Consumption 900 W, 2.5 A

Dimensions $2,790 \text{ (W)} \times 928 \text{ (D)} \times 1,343 \text{ (H)} \text{ mm}$

Weight(Mass) 715 kg

Option Wing scoring, long stacker, barcode kit