

Perfect Binder  
**DPB-500 PUR**

\* PUR gule available  
\* perfect binding,  
1 clamp  
\* 525 cycles/hour



## Specifications

Model DPB-500 PUR

Type	Floor model	
The Number of Clamp	1	
Type of Binding	Binding with a cover, binding without a cover	
Booklet Size		
Book Binding thickness	1 to 51 mm +cover thickness	
Maximum size	360 (length) x 320 (height) mm	
Minimum size	120 (length) x 120 (height) mm	
Book block form	Sheet, single-folded, double-folded	
Paper type	Fine 52 to 157 g/m <sup>2</sup>	
Art/Coated 79 to 157 g/m <sup>2</sup>		
Cover	Feeding method	Belt suction
(Separating air, separator manual non-step adjustment)		
Maximum size	360 (length) x 696 (width) mm	
Minimum size	120 (length) x 250 (width) mm	
Paper type	Fine 81.4 to 302 g/m <sup>2</sup>	
Art/Coated 104.7 to 302 g/m <sup>2</sup>		
Stack height	70 mm	
Maximum Binding Speed	525 cycle/hour	
Milling	Maximum 4 mm	
(Manual 6 step adjustment: 0, 0.5, 1.0, 2, 3, 4 mm)		
Roughening	2 pieces	
Scoring	The number of score	Each 2 on the operator's side and non-operator's side
(spine and hinge)		
Depth adjustment	Manual non-step adjustment	
Ream weight	157g/m <sup>2</sup>	or more
Scoring width	3 to 51 mm	
Nipping	Height adjustment	Manual non-step adjustment
Stacker	Stacking method	Vertical stack
Stack height	Maximum 200 mm	
Ratings	Three-phase, 380 to 415 V, 50/60 Hz	
Power Consumption	900 W, 2.5 A	
Dimensions	2,790 (W) x 928 (D) x 1,343 (H) mm	
Weight(Mass)	715 kg	
Option	Wing scoring, long stacker, barcode kit	