

Suction Collator  
**DSC-10/20**

- 10bins/unit
- Max 2 units connectable
- Flat sheet
- 7,200 sets/h



Features / Performance



Specifications

Machine type vertical suction collator

The number of bins to be collated	10 bins/unit
Maximum number of units connectable	Up to 2 units
Feeding system	Belt suction feed system
Covenyance system	Roller belt conveyance system
Maximum paper loading volume	35 mm in height
Paper size	Min: 139.7 mm(W) x 210 mm(L)
	Max:320 mm(W) x 450 mm(L)
Paper quality	Fine qulaity, Art/coated
Paper weight	Fine quality: 79 to 157 gsm
Art/Coated	: 79 to 157 gsm
Paper type	Sheet
Processing speed	7,200 sets/h
Additional functions	<input type="checkbox"/> Check mode(separation air, pick-up air)
	<input type="checkbox"/> Alternate mode
	<input type="checkbox"/> Block mode(1/2, 1/4)
	<input type="checkbox"/> Interleaf insert mode
	<input type="checkbox"/> Paper eject direction (left/right)
	<input type="checkbox"/> Waiting mode
	<input type="checkbox"/> Manual paper feed(when using LUL-HM)
	<input type="checkbox"/> Reject function(when using LUL-HM)
Power supply	AC100 - 240V, 50/60 Hz
Power consumption	8.1A - 4.2A
Dimensions	630 (W) x 750 (D) x 1,972 (H) mm
Power Supply	745 (W) x 780 (D) x 1,708 (H) mm
Weight	227.5kg